



We help you shine.™



TOTAL ECLIPSE™

FLOOR FINISH

138 TOTAL ECLIPSE™

shine on.

UHS FLOOR FINISH

A polyurethane-fortified acrylic co-polymer floor coating especially suited for concrete, stone and similar hard floor surfaces. Total Eclipse is a clear, non-yellowing formulation that creates an extremely durable and scuff resistant shine. Self-sealing!

Product Packaging¹



PROD CODE: 138FSE
SIZE: 10 litres
ORDER QTY: 2 per case

Product Data:

Description	Acrylic co-polymer emulsion	Coverage	2500 to 3000 ft ² /gal 61 to 74 m ² /liter	Buffability	Excellent
Appearance	Milky white	Fragrance	Slight ammoniacal	Removability ASTM D1792-06	Excellent
Non-volatile solids ASTM D2834-95 (2008)	22%	Slip Resistance UL TM410	Meets requirements	Detergent Resistance ASTM D3207-92 (2008)	Excellent
Specular Gloss (60°) ASTM D1455-87 (2008)	>85	Shelf Life ASTM D1791-93 (2008)	1 year	Drying Time	About 30 minutes
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise	Density ASTM D1475-98 (2008)	8.5 lb/gal @ 68°F 1.02 kg/L @ 20°C	Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

MSDS sheets available for download at www.pioneer-eclipse.com

VOC 0.043%
(40 CFR Part 59 Subpart C)



Floor Coating and Finishing materials
as to slip resistance only.

42E6 138_PDS 03/2012

Distributed in New Zealand by



Pioneer Eclipse®

© 2012 Amano Pioneer Eclipse Corporation® • 1 Eclipse Road • PO Box 909 • Sparta, NC 28675 USA
1-800-367-3550 • 1-336-372-8080 • Fax: 1-336-372-2895 • www.pioneer-eclipse.com

Cuts *labor costs* by
reducing scrub & strip cycles.

Recommended Floor Surfaces:

All resilient tile floors and most types of terrazzo, marble, concrete and quarry tile.

Directions for use: INITIAL APPLICATION

1. Remove old coating and sealer.
2. Neutralize floor using a neutral cleaner or EnviroStar Green™ All Purpose Neutralizer.
3. Rinse floor again with clean, cold water and allow to dry.
OPTIONAL: Apply 2 thin coats of sealer to high-traffic areas and old or porous floors.
4. Apply 4-6 coats of Total Eclipse Floor Finish with a clean, synthetic mop. NOTE: Do not exceed an initial application of a combined 6 coats of coating and sealer.
5. Allow floor to dry thoroughly between coats and prior to burnishing.
NOTE: To prevent contamination do not pour unused product from bucket into original container.

Directions for use: ROUTINE MAINTENANCE

1. Sweep floor daily with a dust mop.
2. To clean floor use a mop or automatic scrubber with neutral cleaner.
3. Restore shine as needed with our floor maintainer.
4. Burnish as desired with ultra high speed machine and pad.
5. As needed, perform a deep scrub and re-coat applying an additional 1-2 coats of Total Eclipse Floor Finish.
6. Allow floor to dry thoroughly between coats and prior to burnishing.
7. Strip floor when desired results cannot be achieved with routine maintenance.