



We help you shine.™



REBOUND™

CLEANER AND ENHANCER

PROQUIP NZ LTD - 0800 686 284 - www.proquipnz.co.nz

211 REBOUND™

CLEANER AND ENHANCER

An effective one step cleaner and enhancer. May be applied by automatic scrubber or damp-mop. Cleans and enhances coating for a brilliant wet-look shine when burnished with UHS burnishers.

Product Packaging*



PROD CODE: 211FSE

SIZE: 10 litres

ORDER QTY: 2 per case

Product Data:

Description	Water-based cleaner/enhancer	Fragrance	Lemon-lime	Drying Time	Approximately 15 minutes
Appearance	Clear green	Slip Resistance UL TM410	Meets requirements	Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles
pH ASTM E70-07	9.0 (as supplied) DTC: 10.5 (as supplied)	Shelf Life ASTM D1791-93 (2008)	1 year	VOC (40 CFR Part 59 Subpart C)	0.01% (as supplied) <0.01% (1:32 dilution)
Non-volatile solids ASTM D2834-95 (2008)	11% DT: 22%, DTC: 46%	Density ASTM D1475-98 (2008)	8.4 lb/gal @ 68°F 1.01 kg/L @ 20°C	DT: VOC (40 CFR Part 59 Subpart C)	0.01% (as supplied) <0.01% (1:64 dilution)
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise	DT, DTC: Density ASTM D1475-98 (2008)	8.6 lb/gal @ 68°F 1.03 kg/L @ 20°C	DTC: VOC (40 CFR Part 59 Subpart C)	0.02% (as supplied) <0% (1:128 dilution)

MSDS sheets available for download at www.pioneer-eclipse.com

211_PDS 12/2011



Floor Coating and Finishing materials
as to slip resistance only. 42E6

Distributed in New Zealand by



An **effective** cleaner
and **enhancer** in one.

Recommended Floor Surfaces:

Vinyl composition tile ("VCT") and most types of terrazzo, marble, concrete and quarry tile and treated wood floors.

Directions for use: AUTOMATIC SCRUBBER APPLICATION



DT, DTC: Product to be used only with the AquapHyll™ dilution control system. For recommended **DT 1:64, DTC 1:128 dilution rate**, use AquapHyll™ Portable Plus™ dispenser in bucket setting.

1. Sweep floor with dust mop.
2. Mix REBOUND Cleaner and Enhancer in an automatic scrubber per the following dilution ratio:
1:32 4 US oz per gallon of water (31 ml per 1 liter of water)
3. Scrub and pick up the solution in one pass.
4. Allow floor to dry thoroughly.
5. Burnish floor.

MOP ON APPLICATION

1. Sweep floor with dust mop.
2. Mix REBOUND Cleaner and Enhancer in mop bucket per the following dilution ratio:
1:64 2 US oz per gallon of water (16 ml per 1 liter of water)
3. Damp mop the floor using the solution.
4. Allow floor to dry thoroughly.
5. Burnish floor.

Pioneer Eclipse®

©2011 Amano Pioneer Eclipse Corporation® • 1 Eclipse Road • PO Box 909 • Sparta, NC 28675 USA
1-800-367-3550 • 1-336-372-8080 • Fax: 1-336-372-2895 • www.pioneer-eclipse.com