

396 ECLIPSE™ HD

HEAVY DUTY DEGREASER

A heavy duty degreaser cleaner that rapidly removes the most stubborn greasy soils.

Product Packaging*



PROD CODE: 396MPE SIZE: 4 litres

ORDER QTY: 4 per case

Product Data:

Industrial strength Flash Point >200°F (93°C) Fragrance Sassafras Description ASTM D56-05 (2010) degreaser Shelf Life 5% (as supplied) VOC Appearance Clear dark purple liquid 1 year ASTM D1791-93 (2008) (40 CFR Part 59 Subpart C 1.04% (1:4) 8.9 lb/gal @ 68°F Density VOC 0.58% (1:8) 12.5 (as supplied) 1.07 kg/L @ **ASTM E70-07** ASTM D1475-98 (2008) (40 CFR Part 59 Subpart C) 0.16% (1:32) 20°C Viscosity (Brookfield) Freeze/Thaw Stable <10 centipoise Passes 3 cycles 0.08% (1:64) (40 CFR Part 59 Subpart C) @ 68°F (20°C) ASTM D3209-93 (2008) 396_PDS 10/2011 MSDS sheets available for download at www.pioneer-eclipse.com

Distributed in New Zealand by



Our *industrial strength* that *quickly* degreases.

Recommended Surfaces:

Most washable surfaces.

Directions for use:



Mix ECLIPSE HD Heavy Duty Degreaser with water according to the following dilution:

Light Degreasing of floors, walls, building exteriors, and other surfaces:

1:64 2 US oz per gal water (80 ml per 5 liters water)

Medium Degreasing of baths, showers, and locker room facilities:

1:32 4 US oz per gal water (160 ml per 5 liters water)

Heavy Degreasing and cleaning of floors, metal surfaces, pre-painted surfaces, etc:

1:8 16 US oz per gal water (320 ml per 5 liters water)

Very Heavy Degreasing of food processing equipment & surfaces, machines, and automotive shop areas:

1:4 32 US oz per gal water (1250 ml per 5 liters water)

Apply diluted solution to surfaces by spray, mop, brush, cloth, sponge, automatic scrubber or soak tank. Test for surface compatibility in an inconspicuous area before general use. Allow sufficient contact time for the solution to work properly. Agitate if necessary. Rinse thoroughly with clean water. Food contact surfaces must be rinsed with potable water and then sanitized.

