



We help you shine.™

## FORMULA X-TREME™

ULTRA HIGH PERFORMANCE STRIPPER

PROQUIP NZ LTD - 0800 686 284 - [www.proquipnz.co.nz](http://www.proquipnz.co.nz)

# 549 FORMULA X-TREME™

shine on.

## ULTRA HIGH PERFORMANCE STRIPPER

Concentrated, powerful, non-ammoniated formula cuts through heavy build-up and hard to remove water-based seals in record time. Low odor!

### Product Packaging\*



PROD CODE: 549FSE  
SIZE: 10 litres  
ORDER QTY: 2 per case

Our **cold water** formula  
that's **effective** and fast acting.

### Recommended Floor Surfaces:

Vinyl composition tile ("VCT"), most types of terrazzo, marble and quarry tile.

NOTE: Test floor for color fastness in an inconspicuous area.

### Directions for use:



DTC: Product to be used only with the AquapHyll dilution control system. For recommended **1:32 dilution rate** use AquapHyll™ Wall Mount dispenser in *bucket* setting.

1. Mix Formula X-*Treme* UHP Floor Stripper thoroughly with water until uniform per the following dilution ratios:

#### Light Stripping:

1:40 (3.2 US oz per gallon or 25 ml per 1 liter cold water).

#### Medium Stripping:

1:30 (4.3 US oz per gallon or 34 ml per 1 liter cold water).

#### Heavy Stripping:

1:20 (6.4 US oz per gallon or 50 ml per 1 liter cold water).

2. Apply solution liberally to floor and allow to soak for 5-10 minutes. Do not let floor dry - keep floor wet using additional solution as required.
3. Scrub floor with automatic scrubber or stripping machine. Pick up dirty solution with automatic scrubber or wet vac.
4. Rinse floor twice with neutral cleaner and once with water or use EnviroStar Green™ All Purpose Neutralizer per label instructions.
5. Allow floor to dry thoroughly before applying sealer or coating.

### Product Data:

Description	Non-ammoniated, ultra high performance stripper	Viscosity (Brookfield) @ 68°F (20°C)	<20 centipoise	Density	8.2 lb/gal @ 68°F 0.98 kg/L @ 20°C
Appearance	Clear liquid	Fragrance	None added	VOC	60% (as supplied) (40 CFR Part 59 Subpart C) 2.8% (1:20)
Flash Point	144°F (62°C) ASTM D56-05 (2010)	Shelf Life	2 years ASTM D1791-93 (2008)	VOC	1.90% (1:30) (40 CFR Part 59 Subpart C) 1.43% (1:40)

MSDS sheets available for download at [www.pioneer-eclipse.com](http://www.pioneer-eclipse.com)

549\_PDS 10/2011

Distributed in New Zealand by



Pioneer Eclipse®

©2011 Amano Pioneer Eclipse Corporation® • 1 Eclipse Road • PO Box 909 • Sparta, NC 28675 USA  
1-800-367-3550 • 1-336-372-8080 • Fax: 1-336-372-2895 • [www.pioneer-eclipse.com](http://www.pioneer-eclipse.com)